

SLIM 3 - LED

OUTDOOR > SLIM 3 LED

A linear LED luminaire which illuminates facades uniformly and emphasises their surfaces.
Although buildings fade over time, the proper lighting can add value to them, highlight their uniqueness and make a lasting impression.

Technical Features

- Aluminium body.
- Beam distribution lens.
- Adjustable.
- Safety glass cover.
- Die cast aluminium and caps.
- Silicone sealant.
- Pure light without IR/UV radiation.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10) (only for SLIM 3 - LED).
- Supplied with 3x1mm NEOPRENE 1,5m cable.

Upon request:

Available with highest colour rendering index (CRI)

Product Code: SLIM3_LED1

LED Color Codes

Cool Warm Neutral

Beam Codes

Spot Medium Wide WW

Color Codes

Anodized

Normes



Description

- Beams: Spot, Medium, Wide, WW.
- Adjustable.
- Anodized aluminium body.
- Glass cover.
- CRI: min. 80 / SDCM: 3
- Luminous Efficacy:
6000 K: 135 Lm/Watt
4000 K: 131 Lm/Watt
3000 K: 123 Lm/Watt

Specification

General

Catalogue Chapter	OUTDOOR
Product Family	SLIM 3 - LED
Lamp Category	LED
Fixation	SURFACE
IP	IP 65

Drawings



SLIM 3 - LED

